

| MODELO YM102E | | | | |
|--------------------------------------|----------------------------|------------|-------------|------------|
| Refrigerantes | | R404 | R448A/R449A | R452A |
| Potencia en caballos de fuerza (HP) | | 6 | 6 | 6 |
| Desplazamiento (m ³ /h) | | 20.5 | 20.5 | 20.5 |
| 220V/60Hz/1 Ph | Capacidad (BTU/Hr) | | | |
| | Potencia en Watt (W) | | | |
| | EER (BTU/Wh) | | | |
| 220V&380V& 460V&575V 60Hz/3Ph | Capacidad (BTU/Hr) | 42043 | 43881 | 42042 |
| | Potencia en Watt (W) | 6161 | 5846 | 6161 |
| | EER (BTU/Wh) | 6.82 | 7.51 | 6.82 |
| Electricidad | | | | |
| 220V /60Hz/1Ph | Corriente de operación (A) | | | |
| | MOC(A) | | | |
| | LRA (A) | | | |
| 220V/60Hz/3Ph | Corriente de operación (A) | 19.3 | 18.7 | 19.2 |
| | MOC(A) | 29.4 | 30.8 | 29.4 |
| | LRA (A) | 167 | 167 | 167 |
| 380V /60Hz/3Ph | Corriente de operación (A) | 11 | | |
| | MOC(A) | 17 | | |
| | LRA (A) | 94 | | |
| 460V /60Hz/3Ph | Corriente de operación (A) | 9.4 | 9 | 9.4 |
| | MOC (A) | 14.3 | 14.9 | 14.3 |
| | LRA (A) | 65 | 65 | 65 |
| 575V /60Hz/3Ph | Corriente de operación (A) | 7.3 | | |
| | MOC(A) | 11.2 | | |
| | LRA (A) | 53 | | |
| Calentador del cárter (W) | | 70 | 70 | 70 |
| Medidas de montaje (Inch) | | | | |
| Tubo de descarga (OD) | | 1/2 | 1/2 | 1/2 |
| Tubo de succión (OD) | | 7/8 | 7/8 | 7/8 |
| Dimensiones del producto (MM) | | | | |
| Largo (L) | | 239 | 239 | 239 |
| Ancho (W) | | 239 | 239 | 239 |
| Alto(H) | 1 Fase | 463 | 463 | 463 |
| | 3 Fase | 463 | 463 | 463 |
| Tipo de aceite | | POE | POE | POE |
| Carga de volumen inicia (L) | 1 Fase | 1.6 | 1.6 | 1.6 |
| | 3 Fase | 1.6 | 1.6 | 1.6 |
| Volumen de recarga (L) | 1 Fase | 1.45 | 1.45 | 1.45 |
| | 3 Fase | 1.45 | 1.45 | 1.45 |
| Presión máxima (MPa) | | | | |
| Máximo | | 3.2 | 3.2 | 3.2 |
| Mínimo | | 2.0 | 2.0 | 2.0 |
| Peso(kg) | 1 Fase | | | |
| | 3 Fase | 33 | 32 | 32 |

E.T. -6.7°C, C.T. 48.9°C, R.G. 4.4°C, No Subenfriamiento