

MODELO YM86E				
Refrigerantes		R404	R448A/R449A	R452A
Potencia en caballos de fuerza (HP)		5	5	5
Desplazamiento (m <sup>3</sup> /h)		17.4	17.4	17.4
220V/60Hz/1 Ph	Capacidad (BTU/Hr)	34803	36931	34802
	Potencia en Watt (W)	5514	4980	5514
	EER (BTU/Wh)	6.31	7.42	6.31
220V&380V& 460V&575V 60Hz/3Ph	Capacidad (BTU/Hr)	35161	36931	35160
	Potencia en Watt (W)	5153	4920	5153
	EER (BTU/Wh)	682	7.51	6.82
<b>Electricidad</b>				
220V /60Hz/1Ph	Corriente de operación (A)	26.4	22.8	26.4
	MOC(A)	40.1	40.2	40.1
	LRA (A)	140	140	140
220V/60Hz/3Ph	Corriente de operación (A)	16.6	15.8	16.6
	MOC(A)	25.2	26	25.2
	LRA (A)	136	136	136
380V /60Hz/3Ph	Corriente de operación (A)	9.6		
	MOC(A)	14.6		
	LRA (A)	69		
460V /60Hz/3Ph	Corriente de operación (A)	8	7.6	8
	MOC (A)	12.2	12.5	12.2
	LRA (A)	60	60	60
575V /60Hz/3Ph	Corriente de operación (A)	6.3		
	MOC(A)	9.6		
	LRA (A)	43		
<b>Calentador del cárter (W)</b>		70	70	70
<b>Medidas de montaje (Inch)</b>				
Tubo de descarga (OD)		1/2	1/2	1/2
Tubo de succión (OD)		7/8	7/8	7/8
<b>Dimensiones del producto (MM)</b>				
Largo (L)		239	239	239
Ancho (W)		239	239	239
Alto(H)	1 Fase	463	463	463
	3 Fase	463	463	463
<b>Tipo de aceite</b>		POE	POE	POE
Carga de volumen inicia (L)	1 Fase	1.6	1.6	1.6
	3 Fase	1.6	1.6	1.6
Volumen de recarga (L)	1 Fase	1.45	1.45	1.45
	3 Fase	1.45	1.45	1.45
<b>Presión máxima (MPa)</b>				
Máximo		3.2	3.2	3.2
Mínimo		2.0	2.0	2.0
Peso(kg)	1 Fase	38	38	38
	3 Fase	32	32	32

E.T. -6.7°C, C.T. 48.9°C, R.G. 4.4°C, No Subenfriamiento