

MODELO YM60E				
Refrigerantes		R404	R448A/R449A	R452A
Potencia en caballos de fuerza (HP)		3.5	3.5	3.5
Desplazamiento (m <sup>3</sup> /h)		12.2	12.2	12.2
220V/60Hz/1 Ph	Capacidad (BTU/Hr)	24983	25914	24976
	Potencia en Watt (W)	4030	3545	4030
	EER (BTU/Wh)	6.20	7.31	6.2
220V&380V& 460V&575V 60Hz/3Ph	Capacidad (BTU/Hr)	24983	25863	24976
	Potencia en Watt (W)	3864	3529	3864
	EER (BTU/Wh)	6.47	7.33	6.46
<b>Electricidad</b>				
220V /60Hz/1Ph	Corriente de operación (A)	16.8	16.3	16.8
	MOC(A)	29.4	27	29.4
	LRA (A)	109	109	109
220V/60Hz/3Ph	Corriente de operación (A)	12.3	12.1	12.3
	MOC(A)	18.7	17.8	18.7
	LRA (A)	136	136	136
380V /60Hz/3Ph	Corriente de operación (A)	7.8		
	MOC(A)	9.2		
	LRA (A)	69		
460V /60Hz/3Ph	Corriente de operación (A)	6.5	5.8	6.5
	MOC (A)	8.5	8.6	8.5
	LRA (A)	60	60	60
575V /60Hz/3Ph	Corriente de operación (A)			
	MOC(A)			
	LRA (A)			
<b>Calentador del cárter (W)</b>		70	70	70
<b>Medidas de montaje (Inch)</b>				
Tubo de descarga (OD)		1/2	1/2	1/2
Tubo de succión (OD)		7/8	7/8	7/8
<b>Dimensiones del producto (MM)</b>				
Largo (L)		239	239	239
Ancho (W)		239	239	239
Alto(H)	1 Fase	418	418	418
	3 Fase	418	418	418
<b>Tipo de aceite</b>		POE	POE	POE
Carga de volumen inicia (L)	1 Fase	1.4	1.4	1.4
	3 Fase	1.4	1.4	1.4
Volumen de recarga (L)	1 Fase	1.25	1.25	1.25
	3 Fase	1.25	1.25	1.25
<b>Presión máxima (MPa)</b>				
Máximo		3.2	3.2	3.2
Mínimo		2.0	2.0	2.0
Peso(kg)	1 Fase	33	33	33
	3 Fase	31	31	31

E.T. -6.7°C, C.T. 48.9°C, R.G. 4.4°C, No Subenfriamiento